




ELECTRICAL SPECIFICATIONS:

1. Impedance: 50Ω ;
2. Frequency: DC~50GHz;
3. VSWR: ≤ 1.35 (max) ;
VSWR: 1.25 (typical) ;
4. Insertion Loss (typical) : 4.10dB;
5. Phase Stability (typical) : $\pm 8^\circ$ @50GHz;
6. Amplitude Stability (typical) : $\pm 0.1\text{dB}$ @50GHz;
7. Velocity of Propagation: 82%;
8. Shielding Effectiveness: $>90\text{dB}$.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Outer Diameter of Cable: 3.1mm;
2. Installation Bend Radius: 15mm;
3. Repeated Bend Radius: 31mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: $-55^\circ\text{C} \sim +165^\circ\text{C}$.

TITLE 2.4mm Male to 2.4mm Male System Interconnect Low-Loss RF Cable Assembly – Use CFS310H Coax			PART NO.	IFCB24-2.4M2.4M-1M
			DWG. NO.	W25042805
			DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ± 0.50 .XX ± 0.10 .X ± 0.20 ANGLES $\pm 1^\circ$			Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com	
SCALE 2:1		VIEW DIRECTION 		
SHEET: 1/1		REV.	V1.0	