



ELECTRICAL SPECIFICATIONS:

1. Impedance: 50 Ω;
2. Frequency: DC~18GHz;
3. VSWR: ≤1.3 (max) ;
VSWR: 1.2 (typical) ;
4. Insertion Loss (typical) : 0.99dB;
5. Phase Stability (typical) : ±3°@18GHz;
6. Amplitude Stability (typical) : ±0.1dB@18GHz;
7. Velocity of Propagation: 83%;
8. Shielding Effectiveness: >90dB.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Outer Diameter of Cable: 7.4mm;
2. Installation Bend Radius: 37mm;
3. Repeated Bend Radius: 74mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: -55℃~+165℃.

TITLE N Male to N Male System Interconnect Low-Loss RF Cable Assembly – Use CFS740H Coax		PART NO.	IFCDN-NMNM-1M
		DWG. NO.	W25042827
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .XX ±0.10 .X ±0.20 ANGLES ±1°		SCALE	VIEW DIRECTION
		1:1	
SHEET: 1/1		REV.	V1.0

Mechanc (Shanghai) Information Technology Co., Ltd.
 www.mechanc.com
 sales@mechanc.com