




ELECTRICAL SPECIFICATIONS:

1. Impedance: 50Ω ;
2. Frequency: DC~26.5GHz;
3. VSWR: ≤ 1.3 (max) ;
VSWR: 1.25 (typical) ;
4. Insertion Loss (typical) : 2.91dB;
5. Phase Stability (typical) : $\pm 5^\circ$ @26.5GHz;
6. Amplitude Stability (typical) : $\pm 0.1\text{dB}$ @26.5GHz;
7. Velocity of Propagation: 81%;
8. Shielding Effectiveness: $>90\text{dB}$.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Outer Diameter of Cable: 2.8mm;
2. Installation Bend Radius: 14mm;
3. Repeated Bend Radius: 28mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: $-55^\circ\text{C} \sim +165^\circ\text{C}$.

TITLE SMA Male to SMA Male System Interconnect Low-Loss RF Cable Assembly – Use CFS280H26 Coax			PART NO.	IFCE35-SMSM-1M
			DWG. NO.	W25042818
			DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .XX ±0.10 .X ±0.20 ANGLES ±1°		SCALE 2:1	Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com	
VIEW DIRECTION 				
SHEET: 1/1		REV.	V1.0	