



ELECTRICAL:

1. Impedance: 50Ω ;
2. Frequency: DC~67GHz;
3. VSWR/Return Loss: ≤ 1.2 ;
4. Insertion Loss: $\leq 0.06 \sqrt{\text{dB}}$;
5. Insulation Resistance: $\geq 5000M \Omega$;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: $-55^{\circ}\text{C} \sim +155^{\circ}\text{C}$;
2. RoHS: Compliant.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

All dimensions are in mm,
all angles are in degrees.

TITLE		PART NO.	1.85-KFD9
1.85mm Female Field Replaceable RF Connector - 2 Hole Flange Mount, 10.2mm Hole Spacing, 0.23mm Pin		DWG. NO.	---
		DATE	---
Mechanc (Shanghai) Information Technology Co., Ltd.			
TOLERANCES UNLESS OTHERWISE SPECIFIED		SCALE	VIEW DIRECTION
X ± 0.50	XX ± 0.10	6:1	
X ± 0.20	ANGLES $\pm 1^{\circ}$		
SHEET: 1/1	REV.	V1.0	
		www.mechanc.com sales@mechanc.com	