



ELECTRICAL:

1. Impedance: 50 Ω;
2. Frequency: DC~67GHz;
3. VSWR/Return Loss: ≤1.2;
4. Insertion Loss: ≤0.06 √ dB;
5. Insulation Resistance: ≥5000M Ω;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

All dimensions are in mm,
all angles are in degrees.

TITLE		PART NO.	1.85-KFD13
1.85mm Female Field Replaceable RF Connector - 4 Hole Flange Mount, 8.64m Hole Spacing, 0.30mm Pin		DWG. NO.	---
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED		Mechanc (Shanghai) Information Technology Co., Ltd	
X ±0.50 XX ±0.10 X ±0.20 ANGLES ±1°	SCALE		
SHEET: 1/1		6:1	REV. V1.0
		www.mechanc.com sales@mechanc.com	