



ELECTRICAL:

1. Impedance: 50 Ω ;
2. Frequency: DC~50GHz;
3. VSWR/Return Loss: ≤1.25;
4. Insertion Loss: ≤0.06 √ dB;
5. Insulation Resistance: ≥5000M Ω ;
6. Dielectric Withstanding Voltage(AC): 325 Vrms.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated; Beryllium Copper, Gold.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55℃ ~ +155℃;
2. RoHS: Compliant.

All dimensions are in mm,
all angles are in degrees.

TITLE		PART NO.	1.85/SSMP-JK1
1.85mm Male to SSMP Female RF Adapter		DWG. NO.	---
		DATE	---
Mechanc (Shanghai) Information Technology Co., Ltd.			
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 XX ±0.10 X ±0.20 ANGLES ±1°		SCALE	VIEW DIRECTION
SHEET: 1/1		6:1	
		REV.	V1.0
		www.mechanc.com sales@mechanc.com	