



**ELECTRICAL:**

1. Impedance: 50 Ω ;
2. Frequency: DC~50GHz;
3. VSWR/Return Loss: ≤1.18;
4. Insertion Loss: ≤0.06 √ fdB;
5. Insulation Resistance: ≥5000M Ω ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

**MATERIAL & PLATING:**

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

**ENVIRONMENTAL & MECHANICAL:**

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

All dimensions are in mm,  
all angles are in degrees.

<b>TITLE</b> <b>2.4mm Female Field Replaceable          RF Connector - 4 Hole Flange Mount,          8.64mm Hole Spacing, 0.51mm Pin</b>		PART NO.	2.4-KFD5
		DWG. NO.	---
		DATE	---
<small>TOLERANCES UNLESS OTHERWISE SPECIFIED          X ±0.50 XX ±0.10          X ±0.20 ANGLES ±1°</small>		SCALE	VIEW DIRECTION
SHEET: 1/1		6:1	
		REV.	V1.0
<b>Mechanc (Shanghai) Information Technology Co., Ltd.</b> <a href="http://www.mechanc.com">www.mechanc.com</a> <a href="mailto:sales@mechanc.com">sales@mechanc.com</a>			