



ELECTRICAL:

1. Impedance: 50 Ω ;
2. Frequency: DC~50GHz;
3. VSWR/Return Loss: ≤ 1.15 ;
4. Insertion Loss: $\leq 0.06 \sqrt{\text{dB}}$;
5. Insulation Resistance: $\geq 5000M \Omega$;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55 $^{\circ}\text{C}$ ~ +155 $^{\circ}\text{C}$;
2. RoHS: Compliant.

All dimensions are in mm,
all angles are in degrees.

TITLE		PART NO.	2.4/1.85-KJ1
2.4mm Female to 1.85mm Male RF Adapter		DWG. NO.	---
		DATE	---
Mechanc (Shanghai) Information Technology Co., Ltd.			
TOLERANCES UNLESS OTHERWISE SPECIFIED		SCALE	VIEW DIRECTION
X ± 0.50 XX ± 0.10 X ± 0.20 ANGLES $\pm 1^{\circ}$		6:1	
SHEET: 1/1		REV.	V1.0
		www.mechanc.com sales@mechanc.com	