



ELECTRICAL:

1. Impedance: 50 Ω ;
2. Frequency: DC~50GHz;
3. VSWR/Return Loss: ≤ 1.18 ;
4. Insertion Loss: $\leq 0.06 \sqrt{f}$ dB;
5. Insulation Resistance: $\geq 5000M \Omega$;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55 $^{\circ}$ C~+155 $^{\circ}$ C;
2. RoHS: Compliant.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

All dimensions are in mm,
all angles are in degrees.

TITLE		PART NO.	2.4-JFD15
2.4mm Male Field Replaceable RF Connector - 4 Hole Flange Mount, 5.64mm Hole Spacing, 0.51mm Pin		DWG. NO.	---
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED		Mechanc (Shanghai) Information Technology Co., Ltd.	
X ± 0.50 XX ± 0.10 X ± 0.20 ANGLES $\pm 1^{\circ}$	SCALE		
	6:1		www.mechanc.com sales@mechanc.com
SHEET: 1/1	REV.	V1.0	