



**ELECTRICAL:**

1. Impedance: 50 Ω;
2. Frequency: DC~50GHz;
3. VSWR/Return Loss: ≤1.2;
4. Insertion Loss: ≤0.06 √ fdB;
5. Insulation Resistance: ≥5000M Ω;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Cable Type: CFT360;
8. Armour Type: AP4060S.

**MATERIAL & PLATING:**

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

**ENVIRONMENTAL & MECHANICAL:**

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

All dimensions are in mm,  
all angles are in degrees.

<b>TITLE</b> 2.4mm Male Straight RF Connector - Fits CFT360 Coaxial Cable - AP4060S Cable Armor			PART NO.	2.4-JCFT360AP4060S-1
			DWG. NO.	---
			DATE	---
<small>TOLERANCES UNLESS OTHERWISE SPECIFIED</small> X ±0.50 XX ±0.10 X ±0.20 ANGLES ±1°			SCALE	VIEW DIRECTION
SHEET: 1/1			6:1	
			REV.	V1.0
Mechanc (Shanghai) Information Technology Co., Ltd. <a href="http://www.mechanc.com">www.mechanc.com</a> <a href="mailto:sales@mechanc.com">sales@mechanc.com</a>				