



**ELECTRICAL:**

1. Impedance: 50 Ω ;
2. Frequency: DC~18GHz;
3. VSWR/Return Loss: ≤1.12;
4. Insertion Loss: ≤0.06 √ dB;
5. Insulation Resistance: ≥5000M Ω ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

**MATERIAL & PLATING:**

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI, PTFE;
3. Outer Conductor: Stainless steel, Passivated.

**ENVIRONMENTAL & MECHANICAL:**

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

All dimensions are in mm,  
all angles are in degrees.

<b>TITLE</b>  2.4mm Male to SMA Male RF Adapter		<b>PART NO.</b>	2.4/SMA-JJ1
		<b>DWG. NO.</b>	---
		<b>DATE</b>	---
<b>TOLERANCES UNLESS OTHERWISE SPECIFIED</b> X ±0.50 XX ±0.10 X ±0.20 ANGLES ±1°		<b>SCALE</b>	<b>VIEW DIRECTION</b>
<b>SHEET: 1/1</b>		6:1	
		<b>REV.</b>	V1.0
Mechanc (Shanghai) Information Technology Co., Ltd. <a href="http://www.mechanc.com">www.mechanc.com</a> <a href="mailto:sales@mechanc.com">sales@mechanc.com</a>			