



#### ELECTRICAL:

1. Impedance:  $50 \Omega$  ;
2. Frequency: DC~40GHz;
3. VSWR/Return Loss:  $\leq 1.17$ ;
4. Insertion Loss:  $\leq 0.06 \sqrt{\text{dB}}$ ;
5. Insulation Resistance:  $\geq 5000M \Omega$  ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Cable Type: CFS360.

#### ENVIRONMENTAL & MECHANICAL:

1. Temperature Range:  $-55^{\circ}\text{C} \sim +155^{\circ}\text{C}$ ;
2. RoHS: Compliant.

#### MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

All dimensions are in mm,  
all angles are in degrees.

TITLE		PART NO.	2.92-KCFS360-1
2.92mm Female Straight RF Connector - Fits CFS360 Coaxial Cable		DWG. NO.	---
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED		Mechanc (Shanghai) Information Technology Co., Ltd.	
X $\pm 0.50$ XX $\pm 0.10$ X $\pm 0.20$ ANGLES $\pm 1^{\circ}$	SCALE 6:1	VIEW DIRECTION 	www.mechanc.com sales@mechanc.com
SHEET: 1/1	REV.	V1.0	