



ELECTRICAL:

1. Impedance: 50 Ω ;
2. Frequency: DC~40GHz;
3. VSWR/Return Loss: ≤ 1.15 ;
4. Insertion Loss: $\leq 0.06 \sqrt{f}$ dB;
5. Insulation Resistance: $\geq 5000M \Omega$;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55 $^{\circ}$ C~+155 $^{\circ}$ C;
2. RoHS: Compliant.

All dimensions are in mm,
all angles are in degrees.

TITLE		PART NO.	2.92-JFD9
2.92mm Male 4-Hole Flange Mount RF Connector - Field Replaceable, 6.35mm Hole Spacing, 0.46mm Pin Diameter		DWG. NO.	---
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED		Mechanc (Shanghai) Information Technology Co., Ltd.	
X ± 0.50 XX ± 0.10 X ± 0.20 ANGLES $\pm 1^{\circ}$	SCALE		
SHEET: 1/1	6:1	REV.	V1.0
		www.mechanc.com sales@mechanc.com	