



ELECTRICAL:

1. Impedance: 50 Ω ;
2. Frequency: DC~40GHz;
3. VSWR/Return Loss: ≤1.17;
4. Insertion Loss: ≤0.06 √fdB;
5. Insulation Resistance: ≥5000M Ω ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Cable Type: CFT360.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Brass, Gold;
Stainless steel, Passivated.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

All dimensions are in mm,
all angles are in degrees.

TITLE 2.92mm Male Right Angle RF Connector - Fits CFT360 Coaxial Cable		PART NO. 2.92-JWCFT360-2
		DWG. NO. ---
		DATE ---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 XX ±0.10 X ±0.20 ANGLES ±1°		SCALE 3:1
VIEW DIRECTION		Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com
SHEET: 1/1	REV.	