



**ELECTRICAL:**

1. Impedance: 50 Ω ;
2. Frequency: DC~40GHz;
3. VSWR/Return Loss: ≤1.25;
4. Insertion Loss: ≤0.06 √ dB;
5. Insulation Resistance: ≥5000M Ω ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Cable Type: CFS360.

**MATERIAL & PLATING:**

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

**ENVIRONMENTAL & MECHANICAL:**

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

All dimensions are in mm,  
all angles are in degrees.

TITLE		PART NO.	2.92-JCFS360-2
<b>2.92mm Male Straight RF Connector - Fits CFS360 Coaxial Cable</b>		DWG. NO.	---
		DATE	---
<small>TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .XX ±0.10 X ±0.20 ANGLES ±1°</small>		Mechanc (Shanghai) Information Technology Co., Ltd.	
SCALE	VIEW DIRECTION	<a href="http://www.mechanc.com">www.mechanc.com</a> <a href="mailto:sales@mechanc.com">sales@mechanc.com</a>	
6:1			
SHEET: 1/1	REV.	V1.0	