



ELECTRICAL:

1. Impedance: 50 Ω;
2. Frequency: DC~40GHz;
3. VSWR/Return Loss: ≤1.17;
4. Insertion Loss: ≤0.06 √ fdB;
5. Insulation Resistance: ≥5000MΩ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Cable Type: CRE086.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Brass, Gold; Stainless steel, Passivated.

All dimensions are in mm,
all angles are in degrees.

TITLE 2.92mm Male Straight RF Connector - Fits CRE086 Coaxial Cable		PART NO.	2.92-J086-2
		DWG. NO.	---
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 XX ±0.10 X ±0.20 ANGLES ±1°		SCALE	VIEW DIRECTION
SHEET: 1/1		6:1	
		REV.	V1.0
Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com			