



### ELECTRICAL:

1. Impedance: 50  $\Omega$  ;
2. Frequency: DC~18GHz;
3. VSWR/Return Loss:  $\leq 1.08$ ;
4. Insertion Loss:  $\leq 0.06$  / dB;
5. Insulation Resistance:  $\geq 5000M \Omega$  ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

### MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PTFE;
3. Outer Conductor: Stainless steel, Passivated.

### ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55 $^{\circ}$ C~+155 $^{\circ}$ C;
2. RoHS: Compliant.

All dimensions are in mm,  
all angles are in degrees.

TITLE		PART NO.	N-KFD13	
N Male Field Replaceable RF Connector - 4 Hole Flange Mount, 8.64mm Hole Spacing		DWG. NO.	---	
		DATE	---	
TOLERANCES UNLESS OTHERWISE SPECIFIED		Mechanc (Shanghai) Information Technology Co., Ltd.  www.mechanc.com sales@mechanc.com		
X $\pm 0.50$ XX $\pm 0.10$ X $\pm 0.20$ ANGLES $\pm 1^{\circ}$	SCALE			VIEW DIRECTION
3:1				
SHEET: 1/1	REV.	V1.0		