




ELECTRICAL:

1. Impedance: $50\ \Omega$;
2. Frequency: DC~18GHz;
3. VSWR/Return Loss: ≤ 1.12 ;
4. Insertion Loss: $\leq 0.06\ \text{dB}$;
5. Insulation Resistance: $\geq 5000M\ \Omega$;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Cable Type: CFS800.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: $-55^{\circ}\text{C} \sim +155^{\circ}\text{C}$;
2. RoHS: Compliant.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PEI;
3. Outer Conductor: Stainless steel, Passivated.

All dimensions are in mm,
all angles are in degrees.

TITLE			PART NO.	N-JCFS800-1
RF Coaxial Connector			DWG. NO.	---
			DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED			Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com	
X	±0.50	XX ±0.10		
X	±0.20	ANGLES ±1°		
SHEET: 1/1		SCALE: 3:1	VIEW DIRECTION	
		REV.	V1.0	