



**ELECTRICAL:**

1. Impedance: 50 Ω ;
2. Frequency: DC~18GHz;
3. VSWR/Return Loss: ≤1.12;
4. Insertion Loss: ≤0.06 √ fdB;
5. Insulation Resistance: ≥5000M Ω ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Cable Type: CFT500MW;
8. Armour Type: AP5780S.

**MATERIAL & PLATING:**

1. Contact: Brass, Gold;
2. Insulation: PTFE;
3. Outer Conductor: Stainless steel, Passivated.

**ENVIRONMENTAL & MECHANICAL:**

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

All dimensions are in mm,  
all angles are in degrees.

TITLE  RF Coaxial Connector		PART NO.	N-JCFT500MWAP5780S-1
		DWG. NO.	---
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 XX ±0.10 X ±0.20 ANGLES ±1°		SCALE	VIEW DIRECTION
SHEET: 1/1		3:1	
		REV.	V1.0
Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com			