



ELECTRICAL:

1. Impedance: 50 Ω ;
2. Frequency: DC~18GHz;
3. VSWR/Return Loss: ≤ 1.08 ;
4. Insertion Loss: ≤ 0.06 $\sqrt{\text{dB}}$;
5. Insulation Resistance: $\geq 5000M\Omega$;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55 $^{\circ}\text{C}$ ~ +155 $^{\circ}\text{C}$;
2. RoHS: Compliant.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PTFE;
3. Outer Conductor: Stainless steel, Passivated.

All dimensions are in mm,
all angles are in degrees.

TITLE		PART NO.	SMA-KFD3
SMA Female 4-Hole Flange Mount RF Connector - Field Replaceable, 8.64mm Hole Spacing, 0.38mm Pin Diameter		DWG. NO.	---
		DATE	---
Mechanc (Shanghai) Information Technology Co., Ltd.			
TOLERANCES UNLESS OTHERWISE SPECIFIED		SCALE	VIEW DIRECTION
X ± 0.50 XX ± 0.10 X ± 0.20 ANGLES $\pm 1^{\circ}$		6:1	
SHEET: 1/1	REV.	V1.0	
		www.mechanc.com sales@mechanc.com	