



ELECTRICAL:

1. Impedance: 50 Ω ;
2. Frequency: DC~26.5GHz;
3. VSWR/Return Loss: ≤ 1.15 ;
4. Insertion Loss: $\leq 0.06 \sqrt{\text{dB}}$;
5. Insulation Resistance: $\geq 5000M \Omega$;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

ENVIRONMENTAL & MECHANICAL:

1. Temperature Range: -55 $^{\circ}\text{C}$ ~ +155 $^{\circ}\text{C}$;
2. RoHS: Compliant.

MATERIAL & PLATING:

1. Contact: Beryllium Copper, Gold;
2. Insulation: PTFE;
3. Outer Conductor: Beryllium Copper, Gold; Brass,Gold.

All dimensions are in mm,
all angles are in degrees.

TITLE		PART NO.	SMP/SMA-KFK1	
SMP Female to SMA Female 2 Hole Flange RF Adapter		DWG. NO.	---	
		DATE	---	
TOLERANCES UNLESS OTHERWISE SPECIFIED		Mechanc (Shanghai) Information Technology Co., Ltd.		
X ± 0.50 XX ± 0.10	SCALE			6:1
X ± 0.20 ANGLES $\pm 1^{\circ}$	VIEW DIRECTION			
SHEET: 1/1	REV.	V1.0	www.mechanc.com sales@mechanc.com	