



### ELECTRICAL:

1. Impedance:  $50 \Omega$  ;
2. Frequency: DC~40GHz;
3. VSWR/Return Loss:  $\leq 1.2$ ;
4. Insertion Loss:  $\leq 0.06 \sqrt{\text{fdB}}$ ;
5. Insulation Resistance:  $\geq 5000M \Omega$  ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Seal:  $\leq 1.013 \times 10^{-3} \text{Pa} \cdot \text{cm}^3/\text{s}(\text{He})$ .

### ENVIRONMENTAL & MECHANICAL:

1. Temperature Range:  $-55^{\circ}\text{C} \sim +155^{\circ}\text{C}$ ;
2. RoHS: Compliant.

### MATERIAL & PLATING:

1. Contact: Kovar alloy, Gold;
2. Insulation: Glass;
3. Outer Conductor: Kovar alloy, Gold.

All dimensions are in mm,  
all angles are in degrees.

<b>TITLE</b> <b>SMPM Male Full Detent Hermetically Sealed RF Connector - Solder Pin Terminal</b>		PART NO.	SMP(M)-JHD2-F
		DWG. NO.	---
		DATE	---
<small>TOLERANCES UNLESS OTHERWISE SPECIFIED</small> X $\pm 0.50$ XX $\pm 0.10$ X $\pm 0.20$ ANGLES $\pm 1^{\circ}$		SCALE	VIEW DIRECTION
SHEET: 1/1		12:1	
		REV.	V1.0
<b>Mechanc (Shanghai) Information Technology Co., Ltd.</b> www.mechanc.com sales@mechanc.com			