



**ELECTRICAL:**

1. Impedance: 50 Ω ;
2. Frequency: DC~50GHz;
3. VSWR/Return Loss: ≤1.3;
4. Insertion Loss: ≤0.06 √ fdB;
5. Insulation Resistance: ≥5000M Ω ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms.

**MATERIAL & PLATING:**

1. Contact: Beryllium Copper, Gold;
2. Insulation: PTFE;
3. Outer Conductor: Stainless steel, Passivated.

**ENVIRONMENTAL & MECHANICAL:**

1. Temperature Range: -55℃~+155℃;
2. RoHS: Compliant.

All dimensions are in mm,  
all angles are in degrees.

TITLE		PART NO.	SSMP-JYD1-F
<b>SSMP Male Full Detent Coaxial Connector - Stub Terminal, Thread-In, Solder</b>		DWG. NO.	---
		DATE	---
<small>TOLERANCES UNLESS OTHERWISE SPECIFIED</small> X ±0.50 XX ±0.10 X ±0.20 ANGLES ±1°		Mechanc (Shanghai) Information Technology Co., Ltd.  www.mechanc.com sales@mechanc.com	
SHEET: 1/1	SCALE: 10:1	VIEW DIRECTION:	REV: V1.0