



#### ELECTRICAL:

1. Impedance:  $50 \Omega$  ;
2. Frequency: DC~40GHz;
3. VSWR/Return Loss:  $\leq 1.3$ ;
4. Insertion Loss:  $\leq 0.06$  / fdB;
5. Insulation Resistance:  $\geq 5000M \Omega$  ;
6. Dielectric Withstanding Voltage(AC): 500 Vrms;
7. Seal:  $\leq 1.013 \times 10^{-3} \text{Pa} \cdot \text{cm}^3/\text{s}(\text{He})$ .

#### ENVIRONMENTAL & MECHANICAL:

1. Temperature Range:  $-55^{\circ}\text{C} \sim +155^{\circ}\text{C}$ ;
2. RoHS: Compliant.

#### MATERIAL & PLATING:

1. Contact: Kovar alloy, Gold;
2. Insulation: Glass;
3. Outer Conductor: Kovar alloy, Gold.

All dimensions are in mm,  
all angles are in degrees.

TITLE		PART NO.	SSMP(M)-JJ1	
SSMP Male to SSMP Male Micro RF Adapter		DWG. NO.	---	
		DATE	---	
TOLERANCES UNLESS OTHERWISE SPECIFIED		Mechanc (Shanghai) Information Technology Co., Ltd.  www.mechanc.com sales@mechanc.com		
X $\pm 0.50$ XX $\pm 0.10$ X $\pm 0.20$ ANGLES $\pm 1^{\circ}$	SCALE			VIEW DIRECTION
	10:1			
SHEET: 1/1	REV.	V1.0		