



ELECTRICAL SPECIFICATIONS:

1. Impedance: 50 Ω;
2. Frequency: DC~67GHz;
3. VSWR: ≤1.35 (max) ;
VSWR: 1.25 (typical) ;
4. Insertion Loss (typical) : 6.67dB;
5. Phase Stability (typical) : ±11°@67GHz;
6. Amplitude Stability (typical) : ±0.10dB@67GHz;
7. Velocity of Propagation: 74%;
8. Shielding Effectiveness: >100dB.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Bending Life of Cable (typical) : 1600;
2. Outer Diameter of Cable: 2.6mm;
3. Repeated Bend Radius: 28mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: -55℃~+165℃.

TITLE		PART NO.	TCA185-1.85M1.85M-1M
1.85mm Male to 1.85mm Male High-Performance RF Test & Measurement Cable Assembly – Use CFT260SH Coax		DWG. NO.	W25043002
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .XX ±0.10 .X ±0.20 ANGLES ±1°		SCALE	2:1
		VIEW DIRECTION	
SHEET: 1/1		REV.	V1.0
Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com			