



ELECTRICAL SPECIFICATIONS:

1. Impedance: 50 Ω;
2. Frequency: DC~40GHz;
3. VSWR: ≤1.3 (max) ;
VSWR: 1.2 (typical) ;
4. Insertion Loss (typical) : 3.11dB;
5. Phase Stability (typical) : ±5°@40GHz;
6. Amplitude Stability (typical) : ±0.05dB@40GHz;
7. Velocity of Propagation: 81%;
8. Shielding Effectiveness: >100dB.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Bending Life of Cable (typical) : 80000;
2. Crush Resistance: 45 kgf/cm;
3. Outer Diameter of Braided Armor: 6.7mm;
4. Repeated Bend Radius: 67mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: -55°C~+125°C.

TITLE		PART NO.	PCA292-AP-2.92M2.92M-1M
2.92mm Male to 2.92mm Male Phase Stable Precision Test RF Cable Assembly - Use CFT420MWP Coax		DWG. NO.	W25042904
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .XX ±0.10 .X ±0.20 ANGLES ±1°		Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com	
SHEET: 1/1		SCALE	VIEW DIRECTION
		1.5:1	
		REV.	V1.0