



ELECTRICAL SPECIFICATIONS:

1. Impedance: $50\ \Omega$;
2. Frequency: DC~6GHz;
3. VSWR: ≤ 1.25 (max) ;
VSWR: 1.2 (typical) ;
4. Insertion Loss (typical) : 0.63dB;
5. Phase Stability (typical) : $\pm 3^\circ @ 6\text{GHz}$;
6. Amplitude Stability (typical) : $\pm 0.05\text{dB} @ 6\text{GHz}$;
7. Velocity of Propagation: 82%;
8. Shielding Effectiveness: $> 100\text{dB}$.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Bending Life of Cable (typical) : 20000;
2. Outer Diameter of Cable: 7.8mm;
3. Repeated Bend Radius: 80mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: $-55^\circ\text{C} \sim +165^\circ\text{C}$.

| | | | |
|---|--|---|----------------|
| TITLE | | PART NO. | TCAS-NMNM-1M |
| N Male to N Male High-Performance RF Test & Measurement Cable Assembly – Use CFT780MH6 Coax | | DWG. NO. | W25043022 |
| | | DATE | --- |
| TOLERANCES UNLESS OTHERWISE SPECIFIED X ± 0.50 .XX ± 0.10 .X ± 0.20 ANGLES $\pm 1^\circ$ | | SCALE | VIEW DIRECTION |
| | | 1:1 | |
| SHEET: 1/1 | | REV. | V1.0 |
| | | Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com | |