



ELECTRICAL SPECIFICATIONS:

1. Impedance: 50 Ω;
2. Frequency: DC~18GHz;
3. VSWR: ≤1.3 (max) ;
VSWR: 1.2 (typical) ;
4. Insertion Loss (typical) : 1.48dB;
5. Phase Stability (typical) : ±3°@18GHz;
6. Amplitude Stability (typical) : ±0.03dB@18GHz;
7. Velocity of Propagation: 82%;
8. Shielding Effectiveness: >100dB.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Bending Life of Cable (typical) : 80000;
2. Crush Resistance: 45 kgf/cm;
3. Outer Diameter of Armored Jacket: 10.8mm;
4. Repeated Bend Radius: 108mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: -40°C~+80°C.

TITLE		PART NO.	PCBN-AS-NMNM-1M
N Male to N Male Phase Stable Precision Test RF Cable Assembly – Use CFT500MWP18 Coax		DWG. NO.	W25042913
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .XX ±0.10 .X ±0.20 ANGLES ±1°		SCALE	VIEW DIRECTION
		1.5:1	
SHEET: 1/1		REV.	V1.0
Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com			