



### ELECTRICAL SPECIFICATIONS:

1. Impedance:  $50 \Omega$ ;
2. Frequency: DC~6GHz;
3. VSWR:  $\leq 1.3$  (max) ;  
VSWR: 1.2 (typical) ;
4. Insertion Loss (typical) : 0.46dB;
5. Phase Stability (typical) :  $\pm 2^\circ$ @6GHz;
6. Amplitude Stability (typical) :  $\pm 0.1$ dB@6GHz;
7. Velocity of Propagation: 83%;
8. Shielding Effectiveness:  $> 90$ dB.

### NOTE:

1. All dimensions are in mm, all angles are in degrees.

### MECHANICAL SPECIFICATIONS:

1. Outer Diameter of Cable: 12mm;
2. Installation Bend Radius: 60mm;
3. Repeated Bend Radius: 120mm.

### ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range:  $-55^\circ\text{C} \sim +105^\circ\text{C}$ .

TITLE		PART NO.	IFCBS-NMNM-1M
N Male to N Male System Interconnect Low-Loss RF Cable Assembly - Use CFS1200H6 Coax		DWG. NO.	W25042842
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X $\pm 0.50$ .XX $\pm 0.10$ .X $\pm 0.20$ ANGLES $\pm 1^\circ$		SCALE	VIEW DIRECTION
		1:1	
SHEET: 1/1		REV.	V1.0
		Mechanc (Shanghai) Information Technology Co., Ltd. www.mechanc.com sales@mechanc.com	