



ELECTRICAL SPECIFICATIONS:

1. Impedance: $50\ \Omega$;
2. Frequency: DC~6GHz;
3. VSWR: ≤ 1.3 (max) ;
VSWR: 1.25 (typical) ;
4. Insertion Loss (typical) : 0.67dB;
5. Phase Stability (typical) : $\pm 2.5^\circ @ 6\text{GHz}$;
6. Amplitude Stability (typical) : $\pm 0.1\text{dB} @ 6\text{GHz}$;
7. Velocity of Propagation: 83%;
8. Shielding Effectiveness: $> 90\text{dB}$.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Outer Diameter of Cable: 7.65mm;
2. Installation Bend Radius: 38mm;
3. Repeated Bend Radius: 76mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: $-55^\circ\text{C} \sim +165^\circ\text{C}$.

TITLE N Male to N Male System Interconnect Low-Loss RF Cable Assembly – Use CFS760MH6 Coax		PART NO.	IFCHN-NMNM-1M
		DWG. NO.	W25042852
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ± 0.50 .XX ± 0.10 .X ± 0.20 ANGLES $\pm 1^\circ$		SCALE	VIEW DIRECTION
		1:1	
SHEET: 1/1		REV.	V1.0

Mechanc (Shanghai) Information Technology Co., Ltd.
 www.mechanc.com
 sales@mechanc.com