



ELECTRICAL SPECIFICATIONS:

1. Impedance: 50 Ω;
2. Frequency: DC~6GHz;
3. VSWR: ≤1.25 (max) ;
VSWR: 1.15 (typical) ;
4. Insertion Loss (typical) : 0.7dB;
5. Phase Stability (typical) : ±2°@6GHz;
6. Amplitude Stability (typical) : ±0.07dB@6GHz;
7. Velocity of Propagation: 83%;
8. Shielding Effectiveness: >90dB.

NOTE:

1. All dimensions are in mm, all angles are in degrees.

MECHANICAL SPECIFICATIONS:

1. Outer Diameter of Cable: 5.6mm;
2. Installation Bend Radius: 28mm;
3. Repeated Bend Radius: 56mm.

ENVIRONMENTAL SPECIFICATIONS:

1. RoHS & REACH: Compliant;
2. Temperature Range: -55℃~+165℃.

TITLE SMA Male to SMA Male System Interconnect Low-Loss RF Cable Assembly – Use CFS550H6 Coax		PART NO.	IFCIS-SMSM-1M
		DWG. NO.	W25042855
		DATE	---
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .XX ±0.10 .X ±0.20 ANGLES ±1°		SCALE	VIEW DIRECTION
		1:1	
SHEET: 1/1		REV.	V1.0

Mechanc (Shanghai) Information Technology Co., Ltd.
 www.mechanc.com
 sales@mechanc.com