

CRE086DS

Semi-Rigid,
Cost-Effective RF Coaxial Cable
Ver: S-A01



Structure & Dimension

	Structure	Dimension (mm)	Material
1	Inner Conductor	0.51	Silver Plated Copper
2	Insulating	1.68	PTFE
3	Outer Conductor	2.18	Seamless Annealed Copper Tube Plating Ternary Alloy

Specification

1	Operating Frequency(GHz)	20
2	Impedance(Ohms)	50
3	Velocity of Propagation	70%
4	Voltage Withstand (Vrms@1min)	1500
5	Shielding Effectiveness(dB)	≥110
6	Weight(g/m)	21
7	Single Bend Radius(mm)	10.00
8	Temperature Range(°C)	-55~+125

Attenuation (Typical@25°C & VSWR=1.0) VS. Frequency VS. Power (VSWR=1.0; 40°C; Sea Level)

Frequency (MHz)	500	1000	5000	10000	20000
Attenuation (dB/m)	0.453	0.636	1.509	2.223	3.291
Average Power (KW)	0.190	0.133	0.057	0.039	0.027



ADD: No. 299 Songqiu Rd,Shanghai China

TEL: +86-021-5466 7179 (+86 150 0036 1136)

WEB: www.mechanc.com

MAIL: hgh@mechanc.com